

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

1 Identification of substance

- **Product details**

- **Trade name:** J-35 OTC

- **Article number:** 83-308130

- **Application of the substance / the preparation**

- **Manufacturer/Supplier:**

Dayton Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Composition/Data on components

- **Chemical characterization**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

67-64-1	acetone	75-100%
1330-20-7	xylene	≤ 10%
100-41-4	ethylbenzene	≤ 2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Hazard description:** May cause eye irritation.

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.
Has a narcotizing effect.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
PHYSICAL HAZARD	0	Reactivity = 0

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** If skin irritation continues, consult a doctor.

(Contd. on page 2)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: J-35 OTC

(Contd. of page 1)

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Seek medical treatment.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
 - Water
 - Water with full jet
- **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
 - Prevent seepage into sewage system, workpits and cellars.
 - Inform respective authorities in case of seepage into water course or sewage system.
- **Measures for cleaning/collecting:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
 - **Information for safe handling:**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
 - **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
 - Store in a cool dry location.
 - Store in a cool location.
 - **Information about storage in one common storage facility:** Store away from incompatible materials.
 - **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: J-35 OTC

(Contd. of page 2)

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm Long-term value: 1188 mg/m ³ , 500 ppm
BEI	

1330-20-7 xylene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm (o-, m-, & p-isomers)
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm
BEI	

100-41-4 ethylbenzene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 543 mg/m ³ , 125 ppm Long-term value: 434 mg/m ³ , 100 ppm
BEI	

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· **General Information**

Form:	Liquid
Color:	Clear

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: J-35 OTC

(Contd. of page 3)

Odor:	Solvent-like
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	56°C (133°F)
· Flash point:	-20°C (-4°F)
· Ignition temperature:	465.0°C (869°F)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20°C (68°F):	233.0 hPa (175 mm Hg)
· Density at 20°C (68°F):	0.778 g/cm ³
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Solvent content:	
Organic solvents:	85.0 %
· Solids content:	15.0 %
· Volatile Organic Compounds:	Not determined

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:**
May cause eye irritation.
Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: J-35 OTC

Irritant

(Contd. of page 4)

12 Ecological information

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**

- **Recommendation:**

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- **DOT regulations:**



- **Hazard class:** 3
- **Identification number:** UN1993
- **Packing group:** II
- **Proper shipping name (technical name):** FLAMMABLE LIQUID, N.O.S. (ACETONE)
- **Label:** 3
- **Limited Quantity Exemption:** No Limited Quantity exemption applies for this shipping class.
- **U.S. Domestic Ground Shipments:** Same as listed for Standard Shipments above.
- **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:** Same as listed for Standard Shipments above.
- **Emergency Response Guide (ERG) Number:** Not determine

- **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 3 Flammable liquids
- **Danger code (Kemler):** 33
- **UN-Number:** 1993
- **Packaging group:** II

(Contd. on page 6)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: J-35 OTC

(Contd. of page 5)

· **Description of goods:** 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE)

· **Maritime transport IMDG:**



· **IMDG Class:** 3
 · **UN Number:** 1993
 · **Label:** 3
 · **Packaging group:** II
 · **EMS Number:** F-E,S-E
 · **Marine pollutant:** No
 · **Propper shipping name:** FLAMMABLE LIQUID, N.O.S. (ACETONE)

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3
 · **UN/ID Number:** 1993
 · **Label:** 3
 · **Packaging group:** II
 · **Propper shipping name:** FLAMMABLE LIQUID, N.O.S. (ACETONE)

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

1330-20-7	xylene	≤10%
100-41-4	ethylbenzene	≤2.5%
108-88-3	toluene	≤1%
71-43-2	benzene	≤0.01%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

71-43-2 benzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

71-43-2 benzene

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: J-35 OTC

(Contd. of page 6)

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	
71-43-2	benzene	

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	D
1330-20-7	xylene	D
100-41-4	ethylbenzene	D
108-88-3	toluene	D
71-43-2	benzene	A

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
71-43-2	benzene	1

· **NTP (National Toxicology Program)**

71-43-2	benzene	K
---------	---------	---

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
1330-20-7	xylene	A4
108-88-3	toluene	A4
71-43-2	benzene	A1

· **MAK (German Maximum Workplace Concentration)**

71-43-2	benzene	1
---------	---------	---

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

71-43-2	benzene	
---------	---------	--

· **OSHA-Ca (Occupational Safety & Health Administration)**

71-43-2	benzene	
---------	---------	--

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Xi Irritant

F Highly flammable

· **Risk phrases:**

11 Highly flammable.

36 Irritating to eyes.

67 Vapours may cause drowsiness and dizziness.

(Contd. on page 8)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: J-35 OTC

(Contd. of page 7)

· Safety phrases:

- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 25 Avoid contact with eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 33 Take precautionary measures against static discharges.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 60 This material and its container must be disposed of as hazardous waste.
- 64 If swallowed, rinse mouth with water (only if the person is conscious).

· National regulations:

- Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing MSDS:** Environmental, Health & Safety Department
- Contact:** Environmental, Health & Safety Manager