

Date Revised: 2/1/2016

Supersedes: 5/21/2015

#### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name(s):	Five Star® DP Epoxy Grout / Component C Aggregate Five Star® DP Epoxy Grout PG / Component C Aggregate Five Star® DP Epoxy Grout High Flow / Component C Aggregate Five Star® Easy Mix Grout / Component C Aggregate Five Star® Elastomeric Grout / Component C Aggregate Five Star® Epoxy Grout N / Component C Aggregate Five Star® Epoxy Grout Red N / Component C Aggregate Five Star® Epoxy Novolac Grout / Component C Aggregate Five Star® Epoxy Novolac Grout / Component C Aggregate Five Star® Pile Jacket Epoxy Grout HP/Component C Aggregate Five Star® HP Epoxy Grout / Component C Aggregate Five Star® Rapid Surface Repair Easy Mix/Component C Aggregate Five Star® SP Epoxy Grout / Component C Aggregate
Synonyms:	Aggregate, Component C
Product Use:	Aggregate for reactive polymer construction products. Designed for use with appropriate hardener and resin.
Restrictions on Use:	N/A
Manufacturer/Supplier	Five Star Products, Inc. 60 Parrott Drive Shelton, CT 06484 USA
Phone #:	203-336-7900
Emergency Phone #:	CHEM-TEL 1-800-255-3924 (Outside the U.S. 1-813-248-0585)

#### SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION

Classification:	Eye Damage/Irritation – Category 1
	Sensitization – Respiratory, Category 1
	Carcinogenicity – Category 1A
	Specific Target Organ Systemic Toxicity (Single Exposure) – Cat 3
	Specific Target Organ Toxicity (Repeated Exposure) – Cat 2
Label Flowents (Harand	

#### Label Elements/Hazard Pictograms:



Signal Word:

Warning



Hazard Statements:	Harmful if swallowed H302 May cause respiratory irritation H335 May cause cancer by inhalation H350 May cause damage to organs through prolonged or repeat exposure H373
Precautionary Statements/Prevention:	Do not breathe dust, fume, gas, mist, vapors, or spray, P260. Wash thoroughly after handling, P264. Wear protective gloves, protective clothing, eye protection and face protection, P280. Wear respiratory protection, P284.
Response:	<ul> <li>If swallowed: Rinse mouth. Do NOT induce vomiting, P330, P331.</li> <li>If inhaled: Remove person to fresh air and keep comfortable for breathing, P340.</li> <li>If in eyes: Rinse cautiously with water for several minutes, P351.</li> <li>Remove contact lenses, if present and easy to do. Continue rinsing, P338.</li> <li>Immediately call a poison center or doctor, P310.</li> <li>If skin irritation or rash occurs, P333: Get medical advice/attention, P313.</li> <li>If experiencing respiratory symptoms, P342: Call a poison center or doctor, P310. Wash contaminated clothing before reuse, P363.</li> </ul>
Storage:	Store locked up.
Disposal:	Dispose of contents/container in accordance with applicable regional, national, and local laws and regulations.
Hazards Not Otherwise	

Classified: Not ap	plicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS			
Hazardous Ingredient(s)	Common Name/Synonyms	CAS No.	% wt/wt
Quartz	Silicon Dioxide, Silica Sand, Crystalline Silica	14808-60-7	65-90
Amorphous Silica Mixture	n/a	TS	10-35

#### **SECTION 4: FIRST AID MEASURES**

#### Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms call poison center or doctor.



Date Revised: 2/1/2016

Supersedes: 5/21/2015

Eye Contact:	If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin Contact:	Wash skin thoroughly.
Ingestion:	If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth to an unconscious person.
General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).
Note to Physicians:	Symptoms may not appear immediately. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES		
Flammability and Explosion Information:	Not flammable or combustible by OSHA/WHMIS criteria.	
Sensitivity to Mechanical Impact:	This material is not sensitive to mechanical impact.	
Sensitivity to Static Discharge:	This material is not sensitive to static discharge.	
MEANS OF EXTINCTION		
Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2, or water spray. Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire- control water for later disposal; do not scatter the material.	
Unsuitable Extinguishing Media:	Not available	
Product of Combustion:	Non-combustible	
Protection of Firefighters:	As in any fire, wear self-contained breathing apparatus pressure- demand, MSHA/NIOSH (approved or equivalent) and full protective gear.	

SECTION 6: ACCIDENTAL RELEASE MEASURES		
Emergency Procedures:	Use personal protective equipment. Ensure adequate ventilation. Keep people from spill. Avoid dust formation.	
Personal Precautions:	Avoid inhalation of dust. Do not get into eyes, on skin, or clothing.	
<b>Environmental Precautions:</b>	The environmental impact of this product has not been fully investigated.	



Date Revised: 2/1/2016

Supersedes: 5/21/2015

Methods for Containment:	Cover powder spill with plastic sheet or tarp to minimize spreading. Collect this material into a disposal container by sucking or sweeping up.
Methods for Cleanup:	Pick up and transfer to properly labeled containers.
Other Information:	See Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE	
Handling:	Wear personal protective equipment. Ensure adequate ventilation. Avoid dust formation. Do not breathe dust. Prevent contact with skin, eyes, and clothing. Wash thoroughly after handling.
Storage:	Keep containers tightly closed in a cool, dry, and well-ventilated place. Store locked up.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

Component	CAS No.	ACGIH TLV	OSHA PEL
Quartz	14808-60-7	TWA: 0.025mg/m <sup>3</sup> respirable fraction	30/(%SiO2+2) mg/m <sup>3</sup> TWA, Total Dust;250/%SiO2+5) mppcf TWA, respirable fraction; 10/(%SiO2+2) mg/m <sup>3</sup> TWA, respirable TWA: 0.1 mg/m <sup>3</sup> (vacated)

PEL: Permissible Exposure Limit TLV: Threshold Limit Value

**Engineering Controls:** Not normally required.

#### PERSONAL PROTECTIVE EQUIPMENT (PPE)

Eye/Face Protection:	Tightly fitting safety goggles
Hand Protection:	Impervious gloves. Impervious clothing.
Skin and Body Protection:	Impervious gloves. Impervious clothing.
Respiratory Protection:	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive- pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations:	Handle according to established industrial hygiene and safety practices.



Date Revised: 2/1/2016

Supersedes: 5/21/2015

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Granular Powder	
Color:	Gray, Tan, Pink	
Odor:	None	
Odor Threshold:	None	
Physical State:	Solid, powder	
pH:	1:1 W/O Water=12	
Melting Point / Freezing Point:	n/a	
Initial Boiling Point:	n/a	
Boiling Point:	n/a	
Flash Point:	n/a	
Evaporation Rate:	n/a	
Flammability (solid, gas):	n/a	
Lower Flammability Limit:	n/a	
Upper Flammability Limit:	n/a	
Vapor Pressure:	n/a	
Vapor Density:	n/a	
Relative Density:	2.5-2.8	
Solubility:	Negligible	
Partition Coefficient: n-Octanol/Water:	n/a	
Auto-ignition Temperature:	n/a	
Decomposition Temperature:	n/a	
Viscosity:	n/a	
Percent Volatile, wt.%:	n/a	
VOC Content, wt.%:	n/a	
Density:	n/a	
Coefficient of Water/Oil Distribution:	n/a	

#### SECTION 10: STABILITY AND REACTIVITY

Chemical Stability:	Stable under recommended storage conditions.	
Possibility of Hazardous Reactions:	None under normal processing.	
Conditions to Avoid:	Exposure to water - product may harden on contact with water.	



Incompatible Materials: Strong acids.

SECTION 11: TOXICOLOGICAL INFORMATION			
Information on likely routes of exposure			
Product information:			
Inhalation:	Irritating to respiratory system. Irritating to mucous membranes.		
Eye contact:	Risk of serious damage to eyes.		
Skin contact:	Irritating to skin. May cause allergic skin reaction.		
Ingestion:	Harmful if swallowed.		
Component information:			
Chemical Name: Quartz	LD50 Oral: 500 mg/kg (Rat) ACGIH: A2 – Suspected Human Carcinogen		
IARC: Group 1 – Carcinogenic to humans OSHA: X-present			

Delayed and immediate effects and also chronic effects from short and long term exposure.

#### SECTION 12: ECOLOGICAL INFORMATION

Toxicity:

Aquatic Toxicity:	The environmental impact of this product has not been fully investigated.			
Persistence and Degradability:	No information available.			
<b>Bio-accumulative Potential:</b>	Does not accumulate in organisms			
Mobility in Soil:	No further relevant information available			
Ecotoxical Effects Remark:	No information available.			
Additional Ecological Information:	No information available.			
General Notes:	This statement was deduced from products with a similar structure or composition. Due to available data on eliminability/decomposition and bio-accumulation potential prolonged term damage of the environment cannot be excluded. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Poisonous for fish and plankton in water bodies and toxic for aquatic organisms until alkaline pH is neutralized.			
PBT Assessment:	N/A			
vPvB Assessment:	N/A			
Other Adverse Effects:	No further relevant information available			



#### SECTION 13: DISPOSAL CONSIDERATIONS

#### Waste Treatment Methods

Recommendation:	This material as supplied is not a hazardous waste according to Federal regulations (40CFR261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered.
Uncleaned Packaging Recommendation:	Disposal must be made according to official regulations. Do not re-use empty containers.

#### SECTION 14: TRANSPORT INFORMATION

US DEPARTMENT of TRANSPORTATION (DOT) Proper Shipping Name:	Not regulated
Class:	N/A
UN #:	N/A
Packing Group:	N/A
CANADA Transportation of Dangerous Goods (TDG) Proper Shipping Name:	Not regulated
Class:	N/A
UN #:	N/A
Packing Group:	N/A

#### **SECTION 15: REGULATORY INFORMATION**

CHEMICAL INVENTORIES	
US (TSCA):	The components of this product are in compliance with the chemical notification requirements of TSCA.
CANADA (DSL):	The components of this product are in compliance with the chemical notification requirements of NSN Regulations under CEPA, 1999.
U.S. FEDERAL REGULATIONS	Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the CFR, Part 372.
UNITED STATES:	This SDS has been prepared to meet the US OSHA Hazard Communication Standard, 29 CFR 1910.1200

Five Star	Safety Data Sheet				Date Revised: 2/1/2016 Supersedes: 5/21/2015		
SARA 311/312 Hazard Categories	Acute health Chronic Healt Fire Hazard - Sudden Relea Reactive Haza	h hazard No ase of Pres	– Yes				
US STATE Right to Know Regulations	Chemical Name	Ŋ	МА	PA	IL	RI	
	Quartz	X	X	x		X	]
California California Prop 65:	This product Chemical Nar		-				nogen

SECTION 16: OTHER INFORMATION		
Disclaimer:	The information contained in this document applies to the specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for one's own particular use.	